3550 liters tank in Stainless 304

52 000 SEK /st exkl moms

Additional information: Laundry detergent; Manhole diameter 500 mm; Adhesions inside; 1 welded pipe inside
Volumetric volume (L): 3.550 L
Pressure in tank: pressure
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Max Overpressure: 0,50 Bar
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: flange DN50
Agitator: yes

Top: 3,50 mm
Cylinder: 3 mm
Bottom: 3,50 mm
Internal diameter tank: 1.308 mm
Cylinder height: 2.250 mm

Total height of tank: 3.500 mm

SKU: 400907

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure
Configuration: single-skin
Max. Service Temperature: 50 °C
Mobile Tank: No, it is not.
Övrig information: Laundry detergent; Manhole diameter 500 mm; Adhesions inside; 1 welded pipe inside; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 0,50 bar
Complete Drainage: Yes
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 3550

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 2,250 mm
Internal diameter: 1.308 mm
Total Height: 3.500 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tjocklek på tank
Bottom: 3,50 mm
Cylinder: 3 mm
Top: 3,50 mm

Mer
Isolated: No