

3586 liter tank in Syrafast 316



259 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Further technical documentation available; sight glass in manhole cover missing; support ring made of Fe; flanges partly made of Fe

Volumetric volume (L): 3.586 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Volume: 202 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Agitator: yes

Number of revolutions: 6 - 40

Power: 3,50

Top: 9,10 mm

Cylinder: 6 mm

Bottom: 6,50 mm

Internal diameter tank: 1.600 mm

Cylinder height: 1.377 mm

Total height of tank: 4.250 mm

SKU: 406022



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 200 °C

Mobile Tank: No, it is not.

Övrig information: Pharmaceutical chemistry; Further technical documents available; Sight glass in the manhole cover is missing; support ring, Fe; Flanges partly made of Fe; we can't give any guarantees about the

Additional Information2: agitator

Agitator: Yes

Overpressure: 3,20 bar

Complete Drainage: No, it is not.

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 3586

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.377 mm
Internal diameter: 1.600 mm
Total Height: 4.250 mm

Stirrer

Power (kW): 3,50
Speed (RPM): 6 – 40

Tjocklek på tank

Bottom: 6,50 mm
Cylinder: 6 mm
Top: 9,10 mm

Mer

Isolated: No