

35895 liter tank in Acid-proof 316



293 000 SEK /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 35.895 L

Pressure in tank: pressure

Design pressure (Bar): 10 Bar

Max. pressure (Bar): 4 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316L (V4A)

Model: horizontal

Configuration: insulated

Heat exchanger: no



Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 316

Gasket manway(s): unknown

Valve: RVS 316L

Gasket shut-off valve (mat): unknown

Fixation point(s): painted steel

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: at the top

Tank outlet: inside Ø 100 mm

Total outlet valve: yes

Top: 6 mm

Cylinder: 6 mm

Bottom: 6 mm

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: riveted

Insulation thickness: 100

Internal diameter tank: 2.200 mm

Distance from outlet to ground: 100 mm

Outer diameter tank: 2.400 mm

Total height of tank: 2.850 mm

Total outer width: 2.450 mm



Total outer length: 10.400 mm

Empty weight tank: 12.000

SKU: 380753

Mer information

Product Description

Material: Acid-resistant 316

Model: Horizontal

New / Used: Used

Operating Pressure in Tank: pressure

Tank design pressure: 10 bars

Configuration: insulated

Max. Service Temperature: 50 °C

Mobile Tank: No, it is not.

Agitator: No

Overpressure: 4 bars

Tank Shape: cylindrical

Complete Drainage: Yes

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316L (V4A)

Volume in liters: 35895



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Tank Outlet: inside Ø 100 mm
Technical Drawing Available: No, it is not.
Outlet Valve: Yes

Material Overview

Material: Acid-resistant 316
Fixing point(s): painted steel
Insulation material: Rockwool
Exterior cladding: RVS 304L

Tank Dimensions

Internal diameter: 2,200 mm
Outlet Height to Ground: 100 mm
Total Height: 2.850 mm
Outer diameter: 2,400 mm

Tjocklek på tank

Bottom: 6 mm
Cylinder: 6 mm
Top: 6 mm

Outer Cladding and Insulation Thickness

External jacket finish: riveted
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Insulation material: Yes

Insulation Thickness OW: 100

Isolated: No

Weight: 12.000