

38000 liters tank in Stainless 304



484 000 SEK /st exkl moms

Additional information: Chemistry; Stand frame made of Fe; manhole cover plated

Volumetric volume (L): 38.000 L

Pressure in tank: pressure

Max. pressure (Bar): 6 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 1.087 L

Max Overpressure: 6 Bar

Max. working temperature: 165 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Power: 11,50

Top: 19 mm

Cylinder: 12 mm

Bottom: 16 mm

Internal diameter tank: 3.180 mm

Cylinder height: 3.900 mm

Total height of tank: 8.800 mm

SKU: 402572

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 165 °C

Mobile Tank: No, it is not.

Övrig information: Chemistry; Stand frame made of Fe; manhole cover plated; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 6 bars

Complete Drainage: Yes

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 38000

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 3,900 mm

Internal diameter: 3.180 mm

Total Height: 8.800 mm

Stirrer

Power (kW): 11,50

**Tjocklek på tank**

Bottom: 16 mm

Cylinder: 12 mm (0,5 in.)

Top: 19 mm

Mer

Isolated: No