

390 liter tank in Acid-proof 316



187 000 SEK /st exkl moms

Additional information: 1 pump is included in the scope of delivery (no guarantee of functionality)

Volumetric volume (L): 390 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 26 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN40 DIN 11851

Agitator: yes

Power: 0,37

Cylinder: 8 mm

Bottom: 6 mm

Internal diameter tank: 650 mm

Outer diameter tank: 810 mm

Cylinder height: 990 mm

Total height of tank: 2.050 mm

SKU: 440666



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 150 °C

Mobile Tank: No, it is not.

Övrig information: Pharmacy; 1 pump is included in delivery (no guarantee of functionality); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 4 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 390

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 990 mm
Internal diameter: 650 mm
Total Height: 2,050 mm
Outer diameter: 810 mm

Stirrer

Power (kW): 0,37

Tjocklek på tank

Bottom: 6 mm
Cylinder: 8 mm

Mer

Heat Exchanger: RVS 304
Isolated: Yes