

400 liter tank in stainless steel 304



97 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 400 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes



Mobile tank: no

Top type: half hinging lid

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 3 adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the middle part of the cylinder

Height HE: 550 mm

Water pressure HE: 2 Bar

Type of HE on the bottom: dimple-jacket

Water pressure HE: 2 Bar

Heat exchanger: RVS 316

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: no

Tank outlet: inside Ø 72 mm

Outlet type: DIN11851

Agitator: yes

Agitator type: gate

Position engine: at the top

Number of revolutions: 21

Power: 1,50

Voltage: 400 V - three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm



Cylinder: 2

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 40

Internal diameter tank: 850 mm

Distance from outlet to ground: 500 mm

Outer diameter tank: 1.020 mm

Cylinder height: 750 mm

Total height of tank: 2.100 mm

Empty weight tank: 650

SKU: 478575

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: isolert med varmeveksler

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical 15 °

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 400

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 72 mm

Technical Drawing Available: Yes

Outlet Type: DIN11851

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Exterior cladding: RVS 304



Tank Dimensions

Cylinder Height: 750 mm
Internal diameter: 850 mm
Outlet Height to Ground: 500 mm
Total Height: 2.100 mm
Outer diameter: 1,020 mm

Heat exchangers

Height of heat exchanger: 550 mm
Position värmeväxlare: the middle part of the cylinder
Type of Heat Exchanger on Cylinder: dimple jacket
Bottom Heat Exchanger Type: dimple jacket
Water Pressure Heat Exchanger: 2 bars
Water Pressure Heat Exchanger Bottom: 2 bars

Stirrer

Power (kW): 1,50
Motor Position: at the top
Agitator Type: gate
Speed (RPM): 21
Voltage: 400 V – three-phase

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 3 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Insulation material: Rockwool



Mer

Heat Exchanger: RVS 316

Cylinder OW: 2

Insulation Thickness OW: 40

Isolated: Yes

Weight: 650