

4000 liter tank in 304 stainless steel



76 000 SEK /st exkl moms

Additional information: Pharmacy; Tank lid probably removable with 2 hinged segments; 1 manhole diameter approx. 580 mm with loose cover; 1 rectangular opening approx. 385 x 385 in the lid (cover not available); outlet probably DN 40; 4 load cells are included in the scope of delivery (were not taken into account in the specified total height)

Volumetric volume (L): 4.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: available
Agitator: yes
Number of revolutions: 475 / 975
Power: 1.5 / 6.0
Internal diameter tank: 1.850 mm

Cylinder height: 1.650 mm
Total height of tank: 2.850 mm

SKU: 433100

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Pharmacy; Tank lid probably removable with 2 hinged segments; 1 manhole diameter approx. 580 mm with loose cover; 1 rectangular opening approx. 385 x 385 in the lid (cover not available); outlet

Additional Information2: probably DN 40; 4 load cells are included in the scope of delivery (were not taken into account in the specified total height); we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 4000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.650 mm

Internal diameter: 1.850 mm

Total Height: 2.850 mm



Stirrer

Power (kW): 1.5 / 6.0

Speed (RPM): 475 / 975

Mer

Isolated: No