

40000 liter tank in Acid-proof 316



849 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: strong conical bottom 35°; plate thickness 10mm all around; AISI 316 with heavy 32kW agitator; we can't give any guarantees about the agitator

Volumetric volume (L): 40.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: 4 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): aluminium

Manway(s): RVS 316

Fixation point(s): painted steel

Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 600 mm

Agitator: yes

Agitator type: tripad

Position engine: at the top

Power: 32,50

Voltage: three-phase

Top: 10 mm

Cylinder: 10 mm

Bottom: 10 mm

Insulation thickness: 100

Outer diameter tank: 3.400 mm

Cylinder height: 7.200 mm

Total height of tank: 9.600 mm

SKU: 414017



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: strong conical bottom 35°; plate thickness 10mm all around; AISI 316 with heavy 32kW agitator; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: strong conical

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 40000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.



Material Overview

Material: Acid-resistant 316

Fixing point(s): painted steel

Insulation material: Rockwool

Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Exterior cladding: aluminum

Tank Dimensions

Cylinder Height: 7.200 mm

Total Height: 9.600 mm

Outer diameter: 3,400 mm

Stirrer

Power (kW): 32,50

Motor Position: at the top

Agitator Type: tripad

Voltage: three-phase

Tjocklek på tank

Bottom: 10 mm

Cylinder: 10 mm

Top: 10 mm

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Insulation Thickness OW: 100

Isolated: Yes