

40000 liters tank in Stainless 304



281 000 SEK /st exkl moms

Additional information: there is a dent in the insulation cladding, the inner tank itself is ok

Volumetric volume (L): 40.000 L

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Shape of tank: cylindrical

Total discharge: yes

Insulation material: rockwool



Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 300 mm x H 400 mm

Tank outlet: inside Ø 100 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 25/51

Power: 7,50

Voltage: three-phase

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Distance from outlet to ground: 1.100 mm

Outer diameter tank: 3.850 mm

Total height of tank: 8.300 mm

Empty weight tank: 4.600

SKU: 381077



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: there is a dent in the insulation cladding, the inner tank itself is ok; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 40000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 100 mm

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Exterior cladding: RVS 304



Tank Dimensions

Outlet Height to Ground: 1.100 mm

Total Height: 8.300 mm

Outer diameter: 3.850 mm

Stirrer

Power (kW): 7,50

Motor Position: at the top

Agitator Type: propeller agitator

Speed (RPM): 25/51

Voltage: three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded

Insulation bottom/end caps: Yes

Jacket insulation: Yes

Insulation material: Rockwool

Mer

Insulation material: Yes

Isolated: Yes

Weight: 4.600