

40000 liters tank in Stainless 304



318 000 SEK /st exkl moms

Additional information: food industry; location: Belgium; 1 tank with slight differences in design (such as agitator 7,5 kW - 25/51 rpm); that tank with a dent in the insulation jacket; pipe end cut flush

Volumetric volume (L): 40.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: on skirt

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: in the bottom

Tank outlet: inside Ø 100 mm

Outlet of tank: 100

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 12 / 23

Power: 2.7 / 5.5

Voltage: 380 V - three-phase

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded



Distance from outlet to ground: 1.100 mm

Outer diameter tank: 3.850 mm

Total height of tank: 8.300 mm

Empty weight tank: 4.600

SKU: 389585

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: food industry; location: Belgium; 1 tank with slight differences in design (such as agitator 7,5 kW – 25/51 rpm); that tank with a dent in the insulation jacket; pipe end cut flush; we can't give

Additional Information2: any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: strong conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 40000



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 100 mm
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Outlet Height to Ground: 1.100 mm
Total Height: 8.300 mm
Outer diameter: 3.850 mm

Stirrer

Power (kW): 2.7 / 5.5
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 12 / 23
Voltage: 380 V – three-phase

Outer Cladding and Insulation Thickness

External jacket finish: welded
Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool



Mer

Insulation material: Yes

Isolated: Yes

Weight: 4.600