

420 liter tank in Acid-proof 316



115 000 SEK /st exkl moms

Additional information: pharmacy; One of the pressure vessels is sold with 3 load cells; pneumatic bottom drain valve mounted at the outlet; manhole diameter approx. 300 mm

Volumetric volume (L): 420 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 6 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: clamp

Agitator: yes

Number of revolutions: 2.820

Power: 0,55

Internal diameter tank: 785 mm

Cylinder height: 700 mm

Total outer width: 1.050 mm

Total outer length: 1.150 mm

SKU: 483266



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 130 °C

Mobile Tank: No, it is not.

Övrig information: pharmacy; One of the pressure tanks is sold with 3 load cells; pneumatic bottom drain valve mounted on the outlet; manhole diameter approx. 300 mm; we can't give any guarantees about the

Additional Information2: heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3,20 bar

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 420

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.



Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 700 mm

Internal diameter: 785 mm

Stirrer

Power (kW): 0,55

Speed (RPM): 2.820

Mer

Heat Exchanger: RVS 304

Isolated: Yes