42200 liter tank in GAP/Plast

97 000 SEK /st exkl moms

Article type: second-hand storage tank
Volumetric volume (L): 42.200 L
Max. density P (kg/m³): 1.300
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 30 °C

Min. temperature (°C): -20 °C
Material wet parts: polyester (fiberglass)
Model: vertical
Configuration: insulated
Heat exchanger: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Insulation: yes
Mobile tank: no
Top type: conical
Shape of tank: cylindrical
Bottom type: flat

Total discharge: no
Fixation points: 6 attachment points
Insulation material: PUR
Suitable for food industry: no
Documents included: no

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes
Number of manways: 1
Position of manway: cylinder

Height manhole 1 (mm): 600 mm
Tank outlet: outside Ø 100 mm
Agitator: no, optional
Insulation thickness: 30
Tank capacity top cylinder: 42.200 L

Internal diameter tank: 3.000 mm
Distance from outlet to ground: 500 mm
Outer diameter tank: 3.190 mm
Total height of tank: 6.260 mm
Total outer width: 3.190 mm

SKU: 388262

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: GAP/Plast
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Max. Service Temperature: 30 °C
Maximum Product Density: 1300
Min. Operating Temperature: -20 °C
Mobile Tank: No, it is not.
Agitator: No
Tank Shape: cylindrical
Complete Drainage: No, it is not.
Bottom Type: flat
Heating / Cooling: No
Contact Surface: polyester (fiberglass)
Volume in liters: 42200

Equipment

Product Dokument finns: No
Agitator flange: Yes
Nameplate: Yes
Tank Outlet: outside Ø 100 mm
Technical Drawing Available: Yes

Material Overview

Material: GAP/Plast
Insulation material: PUR

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tank Dimensions
Internal diameter: 3,000 mm
Outlet Height to Ground: 500 mm
Total Height: 6.260 mm
Outer diameter: 3,190 mm

Outer Cladding and Insulation Thickness
Insulation material: PUR

Mer
Insulation Thickness OW: 30
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor