

4370 liter tank in Acid-proof 316



103 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 4.370 L

Pressure in tank: pressure

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 200 °C

Min. temperature (°C): -30 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical



Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 non adjustable feet

Fixation point(s): painted steel

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 80 mm

Total outlet valve: no

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 955

Power: 4,30

Voltage: three-phase

Top: 8 mm

Cylinder: 6 mm

Bottom: 6 mm

Distance from outlet to ground: 70 mm

Outer diameter tank: 1.780 mm

Cylinder height: 1.250 mm

Total height of tank: 2.360 mm



Empty weight tank: 1.500

SKU: 384311

Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: single-skin

Max. Service Temperature: 200 °C

Min. Operating Temperature: -30 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3,20 bar

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: dish

Vacuum Pressure: -1 bar

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 4370



Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Tank Outlet: inside Ø 80 mm

Technical Drawing Available: No, it is not.

Outlet Valve: No, it is not.

Material Overview

Material: Acid-resistant 316

Fixing point(s): painted steel

Tank Dimensions

Cylinder Height: 1.250 mm

Outlet Height to Ground: 70mm

Total Height: 2,360 mm

Outer diameter: 1.780 mm

Stirrer

Power (kW): 4,30

Motor Position: in the cylinder

Agitator Type: propeller agitator

Speed (RPM): 955

Voltage: three-phase

Tjocklek på tank

Bottom: 6 mm

Cylinder: 6 mm

Top: 8 mm

Mer

Isolated: No

Weight: 1.500

