

450 liter tank in Acid-proof 316



48 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Never used, new agitator, new butterfly valve tap; we can't give any guarantees about the agitator

Volumetric volume (L): 450 L

Max. density P (kg/m³): 1

Finish stainless steel: 2B

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Bottom type: flat

Total discharge: yes

Fixation points: 3 adjustable feet

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 680

Power: 0,37

Voltage: three-phase

Cylinder: 3 mm

Bottom: 5 mm

Distance from outlet to ground: 360 mm

Outer diameter tank: 995 mm

Cylinder height: 646 mm

Feet height: 415 mm

Total height of tank: 1.400 mm

Empty weight tank: 250

SKU: 384083



Mer information

Product Description

Food-grade: Yes

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Stainless steel finish: 2b

Configuration: single-skin

Maximum Product Density: 1

Mobile Tank: No, it is not.

Övrig information: Never used, new agitator, new butterfly valve tap; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 316L (V4A)

Volume in liters: 450



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851
Outlet Valve: Yes

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 646 mm
Height on legs: 415 mm
Outlet Height to Ground: 360 mm
Total Height: 1.400 mm
Outer diameter: 995 mm

Stirrer

Power (kW): 0,37
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 680
Voltage: three-phase

Tjocklek på tank

Bottom: 5 mm
Cylinder: 3 mm



Mer

Isolated: No

Weight: 250
