

4500 liter tank in Acid-proof 316



90 000 SEK /st exkl moms

Additional information: Dairy; Smaller dents in the inner cylinder; Manhole cover screw connections incomplete; Tank 1 (F9): outlet DN 65 DIN 11851 with butterfly valve; 1 smaller dent in the insulation jacket; Tank 2 (F7): outlet end (diameter 65 mm) cut off (see photos)

Volumetric volume (L): 4.500 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 17

Power: 1,10

Internal diameter tank: 1.940 mm

Outer diameter tank: 2.060 mm

Cylinder height: 1.400 mm

Total height of tank: 3.200 mm

Empty weight tank: 950

SKU: 405767

Mer information



Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Dairy; Smaller dents in the inner cylinder; Manhole cover screw connections incomplete; Tank 1 (F9): outlet DN 65 DIN 11851 with butterfly valve; 1 smaller dent in the insulation jacket; Tank 2

Additional Information2: (F7): outlet end (diameter 65 mm) cut off (see photos); we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage:

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 4500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.400 mm

Internal diameter: 1,940 mm

Total Height: 3.200 mm

Outer diameter: 2,060 mm



Stirrer

Power (kW): 1,10

Speed (RPM): 17

Mer

Isolated: Yes

Weight: 950