50 liter tank in Acid-proof 316

124 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA
Additional information: delivered with food certificate; *article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm
Volumetric volume (L): 50 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid
With blocking system: yes
Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes

Fixation points: 3 non adjustable feet
Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes
Flange type: Tri-Clamp DN150
CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm
Outlet type: DIN32676 clamp
Total outlet valve: no, optional
Agitator: no, optional
Top: 5 mm

Cylinder: 2,50 mm
Bottom: 2 mm
Internal diameter tank: 406 mm
Distance from outlet to ground: 250 mm
Outer diameter tank: 506 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Cylinder height: 375 mm
Total height of tank: 852 mm
Empty weight tank: 35

SKU: 377471

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 80 °C
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Övrig information: delivered with food certificate; article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without
Additional Information2: options); Ra=<0.8µm
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 20 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 50

Equipment

Agitator flange: Yes
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: Yes
Outlet Type: DIN32676 clamp

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 375 mm
Internal diameter: 406 mm
Outlet Height to Ground: 250 mm
Total Height: 852 mm
Outer diameter: 506 mm

Tjocklek på tank

Bottom: 2 mm
Cylinder: 2,50 mm
Top: 5 mm

Mer

Isolated: No
Weight: 35

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor