# 500 liter tank in 304 stainless steel

16 000 SEK /st exkl moms

**Article type**: second-hand transport tank
**Volumetric volume (L)**: 500 L
**Pressure in tank**: pressure
**Design pressure (Bar)**: 1,43 Bar
**Max. pressure (Bar)**: 1 Bar

**Min. pressure (Bar)**: -0,15 Bar
**Max. temperature (°C)**: 130 °C
**Min. temperature (°C)**: -10 °C
**Material wet parts**: SS AISI 304 (V2A)
**Model**: vertical

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

**Configuration**: single-skin
**Heat exchanger**: no
**Insulation**: no
**Mobile tank**: no
**Top type**: dished

**Shape of tank**: cylindrical
**Bottom type**: strong conical
**Total discharge**: yes
**Fixation points**: 4 stackable frame
**Manway(s)**: RVS 304

**Valve**: RVS 304
**Fixation point(s)**: RVS 304
**Suitable for food industry**: yes
**Documents included**: no
**Technical drawing included**: no

**Registration plate on the tank**: no
**Flange for agitator**: no
**Number of manways**: 1
**Tank outlet**: inside Ø 50 mm
**Outlet type**: DIN11851

**Total outlet valve**: yes
**Distance from outlet to ground**: 360 mm
**Outer diameter tank**: 1.050 mm
**Cylinder height**: 470 mm
**Total height of tank**: 1.400 mm

**Empty weight tank**: 180

**SKU:** 572561



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

# Mer information

**Product Description**

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure
Tank design pressure: 1.43 bar
Configuration: single-skin
Max. Service Temperature: 130 °C
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Agitator: No
Overpressure: 1 bar
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: strong conical
Vacuum Pressure: -0,15 Bar
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 500

**Equipment**

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851
Outlet Valve: Yes



Rodervägen 57
891 78 Bonässund
info@processoverskott.se

**Material Overview**

Material: Stainless steel 304
Fixing point(s): RVS 304

**Tank Dimensions**

Cylinder Height: 470 mm
Outlet Height to Ground: 360 mm
Total Height: 1.400 mm
Outer diameter: 1.050 mm

**Mer**

Isolated: No
Weight: 180

**PROCESSÖVERSKOTT AB**

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor