500 liter tank in Acid-proof 316

83 000 SEK /st exkl moms

Additional information: Acids and alkalis; 3 support brackets, Aisi 304; 1 hand hole DN 200 in the upper bottom; Metallic discolouration inside
Volumetric volume (L): 500 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 156 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 6 Bar

Max. working temperature: 156 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: 48
Cylinder: 5 mm
Bottom: 5 mm
Internal diameter tank: 800 mm

Outer diameter tank: 1.000 mm
Total height of tank: 1.600 mm
Empty weight tank: 650

SKU: 420326

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 156 °C
Mobile Tank: No, it is not.
Övrig information: Acids and alkalis; 3 support brackets, Aisi 304; 1 hand hole DN 200 in the upper bottom; Metallic discolouration inside; we can't give any guarantees about the heating/cooling jacket
Agitator: No
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 500

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Internal diameter: 800 mm
Total Height: 1.600 mm
Outer diameter: 1.000 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tjocklek på tank
Bottom: 5 mm
Cylinder: 5 mm

Mer
Isolated: Yes
Weight: 650

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se