

500 liter tank in Acid-proof 316



251 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type OTP-SC

Volumetric volume (L): 500 L

Max. density P (kg/m³): 1.200

Finish stainless steel: 2B

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 150 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: yes

Top type: large separat lid

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 casters

Manway(s): RVS 316

Gasket manway(s): silicone

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 40 mm

Outlet type: DIN32676

Total outlet valve: no, optional

Agitator: no, optional

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 702 mm

Distance from outlet to ground: 264 mm

Outer diameter tank: 710 mm

Cylinder height: 1.250 mm

Total height of tank: 1.958 mm

Empty weight tank: 205



SKU: 415676

Mer information

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: pressure
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature:
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: Yes
Agitator: No
Overpressure: 3 bars
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: dish
Vacuum Pressure: -1 bar
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 500



Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: Yes
Outlet Type: DIN32676

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 1.250 mm
Internal diameter: 702 mm
Outlet Height to Ground: 264 mm
Total Height: 1.958 mm
Outer diameter: 710 mm

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm

Mer

Isolated: No
Weight: 205