500 liter tank in Acid-proof 316

63 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type BBT-ES-SL
Volumetric volume (L): 500 L
Max. density P (kg/m³): 1.200

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Ra inner weld: 0,80
Pressure in tank: pressure

Design pressure (Bar): 3,40 Bar
Max. pressure (Bar): 2 Bar
Max. temperature (°C): -10 °C
Min. temperature (°C): 130 °C
Material wet parts: SS AISI 316L (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet

Manway(s): RVS 316
Gasket manway(s): EPDM
Valve: RVS 316
Gasket shut-off valve (mat): EPDM
Fixation point(s): RVS 304L

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Inspection of: TUV

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
CIP spray ball: no, optional

Tank outlet: inside Ø 50 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Outlet type: DIN11851 male
Total outlet valve: yes
Agitator: no, optional
Top: 2 mm

Cylinder: 2 mm
Bottom: 2,50 mm
Distance from outlet to ground: 200 mm
Outer diameter tank: 797 mm
Cylinder height: 800 mm

Total height of tank: 1.476 mm
Empty weight tank: 180

SKU: 381284

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank: pressure
Tank design pressure: 3,40 bar
Configuration: single-skin
Max. Service Temperature: -10 °C
Maximum Product Density: 1200
Min. Operating Temperature: 130 °C
Mobile Tank: No, it is not.
Agitator: No
Overpressure: 2 bars
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: dish
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 500

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male
Outlet Valve: Yes

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 800 mm
Outlet Height to Ground: 200 mm
Total Height: 1.476 mm
Outer diameter: 797 mm

Tjocklek på tank

Bottom: 2,50 mm
Cylinder: 2 mm
Top: 2 mm

Mer

Isolated: No
Weight: 180

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor