

500 liter tank in Acid-proof 316





59 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL

Volumetric volume (L): 500 L

Max. density P (kg/m³): 1.200

Ra inner weld: 1,60

Finish stainless steel: 2b

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 %

Shape of tank: cylindrical

Bottom type: conical 15 %

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 316

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 240 mm

Outer diameter tank: 796 mm

Cylinder height: 1.000 mm

Total height of tank: 1.635 mm

Empty weight tank: 80

SKU: 375992

Mer information



Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Maximum Product Density: 1200
Mobile Tank: No, it is not.
Agitator: No
Ra Internal Weld: 1,60
Tank Shape: cylindrical
Complete Drainage:
Bottom Type:
Heating / Cooling: No
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 500

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304



Tank Dimensions

Cylinder Height: 1.000 mm

Outlet Height to Ground: 240 mm

Total Height: 1.635 mm

Outer diameter: 796 mm

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 2,50 mm

Mer

Isolated: No

Weight: 80