

## 5000 liter tank in 304 stainless steel



121 000 SEK /st exkl moms

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

**Volumetric volume (L):** 5.000 L

**Pressure in tank:** ATM - atmospheric

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes



**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Type of HE on the cylinder:** half pipe welded onto the outside of the innertank

**Position HE:** the complet cilinder

**Type of HE on the bottom:** half pipe welded onto the outside of the innertank

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Hinged lid:** yes

**Tank outlet:** inside Ø 60 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Power:** 1,20

**Voltage:** 400 V - three-phase

**Current:** 3,10

**Distance from outlet to ground:** 670 mm

**Outer diameter tank:** 2.000 mm

**Cylinder height:** 2.050 mm

**Total height of tank:** 3.800 mm



**Empty weight tank:** 1.050

**SKU:** 416561

## Mer information

### Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5000



## Equipment

Product Dokument finns: No, it is not.  
Agitator flange: No  
Nameplate: No, it is not.  
Food-grade: Yes  
Tank Outlet: inside Ø 60 mm  
Technical Drawing Available: No, it is not.

## Material Overview

Material: Stainless steel 304  
Fixing point(s): RVS 304

## Tank Dimensions

Cylinder Height: 2,050 mm  
Outlet Height to Ground: 670 mm  
Total Height: 3,800 mm  
Outer diameter: 2,000 mm

## Heat exchangers

Position värmeväxlare: the complete cylinder  
Type of Heat Exchanger on Cylinder: half pipe welded onto the outside of the innertank  
Bottom Heat Exchanger Type: half pipe welded onto the outside of the innertank

## Stirrer

Power (kW): 1,20  
Motor Position: at the top  
Agitator Type: propeller agitator  
Voltage: 400 V – three-phase

## Mer

Isolated: Yes  
Weight: 1.050