

5000 liter tank in 304 stainless steel



91 000 SEK /st exkl moms

Additional information: Cosmetics; 1 level indicator each (incomplete); some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)



Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN25 DIN 11851

Agitator: yes

Number of revolutions: 282

Power: 1,10

Cylinder: 4 mm

Bottom: 4 mm

Total height of tank: 2.750 mm

Total outer width: 1.620 mm

Total outer length: 1.750 mm

Empty weight tank: 750

SKU: 402047

Mer information



Product Description

Material: Stainless steel 304

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Cosmetics; 1 level indicator each (incomplete); some residues of previous content; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Total Height: 2,750 mm

Stirrer

Power (kW): 1,10

Speed (RPM): 282

Tjocklek på tank

Bottom: 4 mm

Cylinder: 4 mm



Mer

Isolated: No

Weight: 750