

5000 liter tank in 304 stainless steel



156 000 SEK /st exkl moms

Additional information: Dairy; Possibly dents in the insulating jacket

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN65 DIN 11851

Agitator: yes

Number of revolutions: 34

Power: 2,20

Top: 3 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Internal diameter tank: 1.600 mm

Outer diameter tank: 1.710 mm

Cylinder height: 2.500 mm

Total height of tank: 4.650 mm

SKU: 405731



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Dairy; Possibly dents in the insulating jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5000

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 2.500 mm

Internal diameter: 1.600 mm

Total Height: 4.650 mm

Outer diameter: 1.710 mm

**Stirrer**

Power (kW): 2,20

Speed (RPM): 34

Tjocklek på tank

Bottom: 2,50 mm

Cylinder: 2 mm

Top: 3 mm

Mer

Isolated: Yes