

5000 liter tank in 304 stainless steel



114 000 SEK /st exkl moms

Additional information: chemistry; 2 vessels (6169-3+5) with broken intermediate flange on gearbox; some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: pressure

Max. temperature (°C): 60 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no



Mobile tank: no

Total discharge: yes

Volume: 98 L

Max Overpressure: 10 Bar

Max. working temperature: 60 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 26 - 101

Power: 6,80

Top: 9 mm

Cylinder: 6 mm

Bottom: 5,40 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.750 mm

Total height of tank: 4.200 mm

SKU: 391541



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 60 °C

Mobile Tank: No, it is not.

Övrig information: chemistry; 2 tanks (6169-3+5) with broken intermediate flange at the gear; some residues of previous content; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5000

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.750 mm

Internal diameter: 1.800 mm

Total Height: 4.200 mm

**Stirrer**

Power (kW): 6,80

Speed (RPM): 26 – 101

Tjocklek på tank

Bottom: 5,40 mm

Cylinder: 6 mm

Top: 9mm

Mer

Heat Exchanger: RVS 304

Isolated: No