

5000 liter tank in 304 stainless steel



67 000 SEK /st exkl moms

Additional information: Spirits; Manhole diameter upper bottom approx. 425 mm, manhole cylinder approx. 310 x 425 mm; small dents in the cylinder

Volumetric volume (L): 5,000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 1,390

Power: 0.55

Top: 2 mm

Cylinder: 1.90 mm

Bottom: 2.50 mm

Internal diameter tank: 1,890 mm

Cylinder height: 1,690 mm

Total height of tank: 2.450 mm

SKU: 455096

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Spirits; Diameter manhole upper bottom appr. 425 mm, manhole cylinder appr. 310 x 425 mm; small dents in the cylinder; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.690 mm

Internal diameter: 1.890 mm

Total Height: 2,450 mm

Stirrer

Power (kW): 0,55

Speed (RPM): 1.390

**Tjocklek på tank**

Bottom: 2,50 mm

Cylinder: 1,90 mm

Top: 2 mm

Mer

Isolated: No