

5000 liter tank in Acid-proof 316



107 000 SEK /st exkl moms

Additional information: Food industry; 1 dent in the inner tank (overpressure of the no longer functional heating jacket; see photos); insulation jacket with smaller dents and partially detached plates; tank with adhesions inside; Devices for load cells under the feet (3 loose load cells are included in the scope of delivery; these were not taken into account when specifying the total height)

Volumetric volume (L): 5.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: 48
Agitator: yes
Number of revolutions: 450 / 965
Power: 1.1 / 4.4
Internal diameter tank: 1.790 mm

Outer diameter tank: 1.900 mm
Cylinder height: 2.100 mm
Total height of tank: 4.150 mm

SKU: 446723

Mer information



Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Food industry; 1 dent in the inner tank (overpressure of the no longer functional heating jacket; see photos); insulation jacket with smaller dents and partially detached plates; tank with adhesions

Additional Information2:

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 2.100 mm

Internal diameter: 1.790 mm

Total Height: 4.150 mm

Outer diameter: 1.900 mm



Stirrer

Power (kW): 1.1 / 4.4

Speed (RPM): 450 / 965

Mer

Isolated: Yes