

5000 liter tank in Acid-proof 316



209 000 SEK /st exkl moms

Additional information: Food industry; Minor dents in the iso jacket; some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: pressure

Max. temperature (°C): 100 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 5 Bar

Max. working temperature: 100 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 48

Agitator: yes

Number of revolutions: 460

Power: 0,75

Internal diameter tank: 1.700 mm

Outer diameter tank: 1.900 mm

Cylinder height: 2.250 mm

Total height of tank: 4.050 mm

SKU: 408719



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: isolert med varmeveksler

Max. Service Temperature: 100 °C

Mobile Tank: No, it is not.

Övrig information: Food industry; Smaller dents in the insulation jacket; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Additional Information2: agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5000

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 2,250 mm
Internal diameter: 1.700 mm
Total Height: 4.050 mm
Outer diameter: 1.900 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 460

Mer

Heat Exchanger: RVS 304
Isolated: Yes