

5000 liter tank in Acid-proof 316



157 000 SEK /st exkl moms

Additional information: Upper bottom made of stainless steel 304 (1.4301); 4 claws made of Fe; Slight material damage inside the vessel; some residues of previous content; motor-/gear is missing

Volumetric volume (L): 5.000 L

Pressure in tank: pressure

Max. pressure (Bar): 3,20 Bar



Min. pressure (Bar): 3,20 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 16 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Top: 4,50 mm

Cylinder: 10,20 mm

Bottom: 8,30 mm

Internal diameter tank: 1.880 mm

Cylinder height: 1.580 mm

Total height of tank: 3.550 mm

SKU: 407465



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: single jacketed with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Chemistry; Upper bottom, Aisi 304 (1.4301); 4 support brackets, Fe; Slight corrosion of material inside the tank; some residues of previous content; motor-/gear is missing; we can't give any

Additional Information2: guarantees about the agitator

Agitator: Yes

Overpressure: 3,20 bar

Complete Drainage: Yes

Vacuum Pressure:

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.580 mm

Internal diameter: 1.880 mm

Total Height: 3,550 mm

**Tjocklek på tank**

Bottom: 8,30 mm

Cylinder: 10,20 mm

Top: 4,50 mm

Mer

Isolated: No