

5000 liter tank in Acid-proof 316



108 000 SEK /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 5.000 L

Max. density P (kg/m³): 1.000

Pressure in tank: pressure

Design pressure (Bar): 0,49 Bar

Max. pressure (Bar): 0,49 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Wall type: dished

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 100 mm

Outlet type: DIN2576

Total outlet valve: no

Agitator: no

Top: 4 mm

Cylinder: 4 mm

Bottom: 4 mm

Outer diameter tank: 1.265 mm

Cylinder height: 3.700 mm

Total height of tank: 1.600 mm

Total outer length: 4.500 mm

Empty weight tank: 800

SKU: 451196



Mer information

Product Description

Material: Acid-resistant 316

Model: Horizontal

New / Used: Used

Operating Pressure in Tank: pressure

Tank design pressure: 0,49 bar

Configuration: single-skin

Max. Service Temperature: 50 °C

Maximum Product Density: 1000

Mobile Tank: No, it is not.

Agitator: No

Overpressure: 0,49 bar

Tank Shape: cylindrical

Complete Drainage:

Pressure Vessel: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Tank Outlet: inside Ø 100 mm

Technical Drawing Available: No, it is not.

Outlet Type: DIN2576

Outlet Valve: No, it is not.



Material Overview

Material: Acid-resistant 316

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 3,700 mm

Total Height: 1.600 mm

Outer diameter: 1.265 mm

Tjocklek på tank

Bottom: 4 mm

Cylinder: 4 mm

Top: 4 mm

Mer

Isolated: No

Weight: 800