50000 liter tank in Acid-proof 316

304 000 SEK /st exkl moms

Additional information: Steel feet cut off below the mounting flange (see pictures); inside with reinforcement rings (see pictures)
Volumetric volume (L): 50.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN100
Internal diameter tank: 3.600 mm
Cylinder height: 4.050 mm

Total height of tank: 6.000 mm
Empty weight tank: 7.000

SKU: 567560

Mer information

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: single-skin
Max. Service Temperature: 200 °C
Mobile Tank: No, it is not.
Övrig information: Chemistry; Steel feet cut off below the mounting flange (see pictures); inside with reinforcement rings (see pictures)
Agitator: No
Overpressure: 3,20 bar
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: No
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 50000

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 4.050 mm
Internal diameter: 3.600 mm
Total Height: 6,000 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer
Isolated: No
Weight: 7.000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor