

50000 liters tank in Stainless 304



289 000 SEK /st exkl moms

Additional information: Dairy; Manhole appr. 410 x 480 mm; smaller dents in the insulation jacket; pipe end cut flush

Volumetric volume (L): 50.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 100

Number of revolutions: 460

Power: 2,20

Internal diameter tank: 2.690 mm

Outer diameter tank: 2.850 mm

Cylinder height: 8.750 mm

Total height of tank: 10.010 mm

SKU: 404405

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: Dairy; Manhole appr. 410 x 480 mm; smaller dents in the insulation jacket; pipe end cut flush

Agitator: No

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 50000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 8.750 mm

Internal diameter: 2,690 mm

Total Height: 10.010 mm

Outer diameter: 2.850 mm

Stirrer

Power (kW): 2,20

Speed (RPM): 460



Mer

Isolated: Yes