

50000 liters tank in Stainless 304



406 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type TZN-SL

Volumetric volume (L): 50.000 L

Max. density P (kg/m³): 1.000

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no



Insulation: no

Mobile tank: no

Top type: conical 13 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 6 non adjustable feet

Manway(s): RVS 304

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Inspection of: No Documentation

Flange for agitator: no

Number of manways: 2

Position of manway: headside

Height manhole 1 (mm): 500 mm

Position 2nd manway: cylinder

Height manhole 2 (mm): 440 x 308 mm

Tank outlet: inside Ø 80 mm

Outlet type: DIN 11851

Top: 2,50 mm

Cylinder: 2,50 mm

Bottom: 4 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.984 mm

Cylinder height: 7.000 mm

Height of top: 382 mm

Height of bottom: 600 mm

Feet height: 1.000 mm

Total height of tank: 8.382 mm



Empty weight tank: 1.850

SKU: 375023

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Maximum Product Density: 1000

Mobile Tank: No, it is not.

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical 20 °

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 50000



Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Inspected by: No Documentation
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN 11851

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 7,000 mm
Height on legs: 1.000 mm
Outlet Height to Ground: 400 mm
Total Height: 8.382 mm
Outer diameter: 2.984 mm

Tjocklek på tank

Bottom: 4 mm
Cylinder: 2,50 mm
Top: 2,50 mm

Mer

Isolated: No
Weight: 1.850