

5100 liter tank in Stainless 304



71 000 SEK /st exkl moms

Additional information: Fruit juice industry; Attention: Contrary to the information on the nameplate, this tank cannot be heated/cooled; The tank was probably formerly equipped with a heating-coil inside (unlike the welded brackets, this is no longer present); Manhole diameter approx. 420 mm; Insulation is cut out in several places; small dents in the insulation jacket; The outlet pipe tapers towards the tank to an internal pipe diameter of approx. 80 mm; some residues of previous content; Metallic discolouration inside



Volumetric volume (L): 5.100 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 95 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 75 L
Max Overpressure: 8 Bar
Max. working temperature: 169 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN100 DIN 11851

Internal diameter tank: 1.890 mm
Outer diameter tank: 2.000 mm
Total height of tank: 3.050 mm

SKU: 422441

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Max. Service Temperature: 95 °C

Mobile Tank: No, it is not.

Övrig information: Fruit juice industry; Attention: Contrary to the information on the nameplate, this tank cannot be heated/cooled; The tank was probably formerly equipped with a heating-coil inside (unlike the

Additional Information2:

Agitator: No

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5100

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Internal diameter: 1.890 mm

Total Height: 3.050 mm

Outer diameter: 2,000 mm



Mer

Isolated: Yes