


51300 liters tank in Stainless 304



438 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K5-SL

Volumetric volume (L): 51.300 L

Max. density P (kg/m³): 1.350

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304L (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Wall type: conical 20 °

Total discharge: yes

Fixation points: 6 adjustable feet

Manway(s): RVS 304L

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

CIP spray ball: no, optional

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 4 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.984 mm



Cylinder height: 7.000 mm

Feet height: 1.005 mm

Total height of tank: 8.450 mm

Empty weight tank: 1.800

SKU: 385016

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Newly manufactured

Operating Pressure in Tank: ATM – atmospheric

Stainless steel finish: 2b

Configuration: single-skin

Max. Service Temperature: 100 °C

Maximum Product Density: 1350

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Agitator: No

Ra Internal Weld: 0,80

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical 20 °

Heating / Cooling: No

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 51300



Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 80 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304L

Tank Dimensions

Cylinder Height: 7,000 mm
Height on legs: 1.005 mm
Outlet Height to Ground: 400 mm
Total Height: 8.450 mm
Outer diameter: 2.984 mm

Tjocklek på tank

Bottom: 4 mm
Cylinder: 2 mm
Top: 2,50 mm

Mer

Isolated: No
Weight: 1.800