520 liter tank in Syrefast 316

62 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: The tank has never been used, in absolute new condition, New agitator.; we can't give any guarantees about the agitator
Volumetric volume (L): 520 L
Ra inner weld: 0,80

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316L (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Shape of tank: cylindrical
Bottom type: flat
Total discharge: yes

Fixation points: 3 adjustable feet
Fixation point(s): RVS 304L
Wet parts agitator(s): SS AISI 316L (V4A)
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851

Total outlet valve: no, optional
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 1.400

Power: 0,75
Voltage: mono
Cylinder: 2 mm
Bottom: 2 mm
Internal diameter tank: 795 mm

Distance from outlet to ground: 260 mm
Outer diameter tank: 905 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Cylinder height: 1.050 mm
Total height of tank: 1.750 mm
Empty weight tank: 90

SKU: 383855

Mer information

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank:
Stainless steel finish: 2b
Configuration: single-skin
Mobile Tank: No, it is not.
Övrig information: The tank has never been used, in absolute new condition, New agitator; we can't give any guarantees about the agitator
Agitator: Yes
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: flat
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 520

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 40 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L
Material vätskeberörd del på omrörare: SS AISI 316L (V4A)

Tank Dimensions

Cylinder Height: 1.050 mm
Internal diameter: 795 mm
Outlet Height to Ground: 260 mm
Total Height: 1.750 mm
Outer diameter: 905 mm

Stirrer

Power (kW): 0,75
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 1.400
Voltage: mono

Tjocklek på tank

Bottom: 2 mm
Cylinder: 2 mm

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer
Isolated: No
Weight: 90

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se