

5200 liter tank in Stainless 304



86 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The agitator drive is missing

Volumetric volume (L): 5.200 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Spray ball: RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown

Valve: RVS 304
Gasket shut-off valve (mat): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Total outlet valve: yes
Internal diameter tank: 1.400 mm

Distance from outlet to ground: 100 mm
Outer diameter tank: 1.600 mm
Cylinder height: 3.430 mm
Total height of tank: 5.120 mm
Empty weight tank: 700

SKU: 489411



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: The agitator drive is missing

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5200

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: No, it is not.

Outlet Type: DIN11851

Outlet Valve: Yes



Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 3,430 mm
Internal diameter: 1.400 mm
Outlet Height to Ground: 100 mm
Total Height: 5.120 mm
Outer diameter: 1.600 mm

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Isolated: Yes
Weight: 700