

## 5200 liter tank in Stainless 304



126 000 SEK /st exkl moms

**item available on order**

**Article type:** brand new storage tank - type K5-SL

**Additional information:** inner surface 0.8μ

**Volumetric volume (L):** 5.200 L

**Max. density P (kg/m³):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2B

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 100 °C



**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 304L (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** conical 15 °

**Shape of tank:** cylindrical

**Bottom type:** conical 15 °

**Total discharge:** yes

**Fixation points:** 4 adjustable feet

**Legs:** Set of baseplates and adjusting pieces included

**Manway(s):** RVS 304L

**Gasket manway(s):** EPDM

**Fixation point(s):** RVS 304L

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Inspection of:** TUV

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Height manhole 1 (mm):** 500 mm

**Tank outlet:** inside Ø 65 mm

**Outlet type:** DIN11851 male

**Total outlet valve:** no, optional

**Agitator:** no, optional

**Top:** 2 mm

**Cylinder:** 2 mm

**Bottom:** 2 mm

**Distance from outlet to ground:** 356 mm

**Outer diameter tank:** 1.592 mm

**Cylinder height:** 2.500 mm

**Feet height:** 620 mm

**Total height of tank:** 3.420 mm

**Empty weight tank:** 305

**SKU:** 380894

## Mer information



## Product Description

Food-grade: Yes  
Material: Stainless steel 304  
Model: Vertical  
New / Used: Newly manufactured  
Operating Pressure in Tank:  
Stainless steel finish: 2b  
Configuration: single-skin  
Max. Service Temperature: 100 °C  
Maximum Product Density: 1200  
Min. Operating Temperature: -10 °C  
Mobile Tank: No, it is not.  
Övrig information: inner surface 0.8µ  
Agitator: No  
Ra Internal Weld: 0,80  
Tank Shape: cylindrical  
Complete Drainage:  
Bottom Type: conical 15 °  
Heating / Cooling: No  
Contact Surface: SS AISI 304L (V2A)  
Volume in liters: 5200

## Equipment

Agitator flange: No  
Nameplate: Yes  
Food-grade: Yes  
Inspected by: TUV  
Tank Outlet: inside Ø 65 mm  
Technical Drawing Available: Yes  
Outlet Type: DIN11851 male

## Material Overview

Material: Stainless steel 304  
Fixing point(s): RVS 304L



## **Tank Dimensions**

Cylinder Height: 2,500 mm

Height on legs: 620 mm

Outlet Height to Ground: 356 mm

Total Height: 3,420 mm

Outer diameter: 1,592 mm

## **Tjocklek på tank**

Bottom: 2 mm

Cylinder: 2 mm

Top: 2 mm

## **Mer**

Isolated: No

Weight: 305