

5236 liter tank in Acid-proof 316



156 000 SEK /st exkl moms

Volumetric volume (L): 5.236 L

Pressure in tank: pressure

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 304 (V2A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 22 L

Max Overpressure: 3 Bar

Max. working temperature: 120 °C

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.990 mm

Cylinder height: 1.500 mm

Total height of tank: 2.770 mm

SKU: 419321



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 120 °C

Mobile Tank: No, it is not.

Agitator: No

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5236

Equipment

Product Dokument finns: No, it is not.

Agitator flange: Yes

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.500 mm

Internal diameter: 1,990 mm

Total Height: 2,770 mm

Tjocklek på tank

Bottom: 3 mm

Cylinder: 3 mm

Top: 2,50 mm



Mer

Heat Exchanger: RVS 304

Isolated: No