

5250 liter tank in Acid-proof 316



58 000 SEK /st exkl moms

Additional information: Chemistry; Cone height approx. 950 mm; 4 feet, Fe screwed to 4 support brackets, Fe; manhole was converted by the previous operator for his purposes; 2 rectangular sheets were welded into the cone bottom (see photos)

Volumetric volume (L): 5.250 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 50

Agitator: yes

Power: 6,80

Internal diameter tank: 1.800 mm

Cylinder height: 1.250 mm

Total height of tank: 4.600 mm

SKU: 435077

Mer information



Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: Chemistry; Cone height approx. 950 mm; 4 feet, Fe screwed to 4 support brackets, Fe; manhole was converted by the previous operator for his purposes; 2 rectangular sheets were welded into the cone

Additional Information2: bottom (see photos); we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5250

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.250 mm

Internal diameter: 1.800 mm

Total Height: 4.600 mm

Stirrer

Power (kW): 6,80

Mer

Isolated: No