5350 liter tank in Acid-proof 316

44 000 SEK /st exkl moms

Additional information: lye; manhole diameter: approx. 500mm; some residues of previous content
Volumetric volume (L): 5.350 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 100
Internal diameter tank: 1.475 mm
Outer diameter tank: 1.620 mm
Cylinder height: 2.920 mm

Total height of tank: 4.000 mm
Total outer width: 2.000 mm

SKU: 424481

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: insulated
Max. Service Temperature: 80 °C
Mobile Tank: No, it is not.
Övrig information: lye; manhole diameter: approx. 500mm; some residues of previous content
Agitator: No
Complete Drainage: Yes
Heating / Cooling: No
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 5350

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 2,920 mm
Internal diameter: 1.475 mm
Total Height: 4,000 mm
Outer diameter: 1,620 mm

Mer

Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor