

54570 liter tank in Acid-proof 316



363 000 SEK /st exkl moms

Additional information: Solvents

Volumetric volume (L): 54.570 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar



Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN100 DIN 11851

Top: 6 mm

Cylinder: 6 mm

Bottom: 10 mm

Internal diameter tank: 3.200 mm

Cylinder height: 5.950 mm

Total height of tank: 7.620 mm

SKU: 476416

Mer information



Product Description

New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: single-skin
Max. Service Temperature: 100 °C
Mobile Tank: No, it is not.
Övrig information: Solvents
Agitator: No
Overpressure: 1 bar
Complete Drainage: Yes
Vacuum Pressure: 0,25 bar
Pressure Vessel: Yes
Heating / Cooling: No
Volume in liters: 54570

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Tank Dimensions

Cylinder Height: 5.950 mm
Internal diameter: 3.200 mm
Total Height: 7.620 mm

Tjocklek på tank

Bottom: 10 mm
Cylinder: 6 mm
Top: 6 mm

Mer

Isolated: No

