

5480 liters tank in Stainless 304



121 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 5.480 L

Pressure in tank: ATM - atmosferic



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: strong conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 adjustable feet

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 500

Position of manway: at the top

Hinged lid: yes

Tank outlet: inside Ø 64 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 950

Power: 5,50

Current: 11.8/6.9

Outer diameter tank: 1.700 mm

Total height of tank: 3.500 mm

SKU: 411683

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: strong conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5480

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 64 mm

Technical Drawing Available: No, it is not.



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Tank Dimensions

Total Height: 3.500 mm

Outer diameter: 1.700 mm

Stirrer

Power (kW): 5,50

Motor Position: in the cylinder

Agitator Type: propeller agitator

Speed (RPM): 950

Mer

Isolated: No