550 liter tank in stainless steel 304

125 000 SEK /st exkl moms

Volumetric volume (L): 550 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Total discharge: yes

Volume: 3 L
Max Overpressure: 5 Bar
Max. working temperature: 80 °C
Fixation point(s): plastic
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes

Number of revolutions: 0-23
Power: 0,75
Internal diameter tank: 820 mm
Cylinder height: 1.034 mm
Total height of tank: 1.780 mm

SKU: 392459

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: single jacketed with heat-exchanger
Max. Service Temperature: 80 °C
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the agitator
Agitator: Yes
Complete Drainage: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 550

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304
Fixing point(s): plastic

Tank Dimensions

Cylinder Height: 1.034 mm
Internal diameter: 820 mm
Total Height: 1.780 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 0-23

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer
Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor