

5500 liter tank in Acid-proof 316



101 000 SEK /st exkl moms

Additional information: lubricant production; Manhole diameter approx. 390 mm; some residues of previous content

Volumetric volume (L): 5.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 1.460

Power: 15

Internal diameter tank: 1.600 mm

Cylinder height: 2.500 mm

Total height of tank: 4.350 mm

SKU: 393935

Mer information



Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: single-skin

Mobile Tank: No, it is not.

Övrig information: lubricant production; diameter manhole appr. 390 mm; some residues of previous content; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: No

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 5500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 2.500 mm

Internal diameter: 1.600 mm

Total Height: 4.350 mm

Stirrer

Power (kW): 15

Speed (RPM): 1.460



Mer

Isolated: No