

5500 liter tank in Stainless 304



58 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The agitator drive is missing, the insulation sheathing has come loose here and there

Volumetric volume (L): 5.500 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): aluminium

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Gasket shut-off valve (mat): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 40 mm

Total outlet valve: yes

Internal diameter tank: 1.450 mm

Distance from outlet to ground: 300 mm

Outer diameter tank: 1.580 mm

Cylinder height: 3.350 mm

Total height of tank: 4.400 mm

Empty weight tank: 600

SKU: 489669



Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: The agitator drive is missing, the insulation sheathing has come loose here and there

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 5500

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 40 mm

Technical Drawing Available: No, it is not.

Outlet Valve: Yes



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Exterior cladding: aluminum

Tank Dimensions

Cylinder Height: 3.350 mm

Internal diameter: 1.450 mm

Outlet Height to Ground: 300 mm

Total Height: 4,400 mm

Outer diameter: 1.580 mm

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Isolated: Yes

Weight: 600