

560 liter tank in Acid-proof 316



31 000 SEK /st exkl moms

Additional information: adhesive production; Loose lid with hinged segment; some residues of previous content; bump at the insulation jacket

Volumetric volume (L): 560 L

Pressure in tank: pressure

Max. temperature (°C): 150 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 10 Bar

Max. working temperature: 150 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN32

Agitator: yes

Number of revolutions: 695

Power: 0,95

Cylinder: 2,50 mm

Bottom: 2,50 mm

Internal diameter tank: 800 mm

Outer diameter tank: 900 mm

Cylinder height: 1.010 mm

Total height of tank: 2.600 mm

SKU: 393884



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 150 °C

Mobile Tank: No, it is not.

Övrig information: adhesive production; loose lid with folding flap segment; some residues of previous content; bump at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't

Additional Information2: give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 560

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.010 mm
Internal diameter: 800 mm
Total Height: 2.600 mm
Outer diameter: 900 mm

Stirrer

Power (kW): 0,95
Speed (RPM): 695

Tjocklek på tank

Bottom: 2,50 mm
Cylinder: 2,50 mm

Mer

Heat Exchanger: RVS 304
Isolated: Yes