

60 liter tank in stainless steel 304



36 000 SEK /st exkl moms

Additional information: Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control cabinet partially incomplete (see photos)

Volumetric volume (L): 60 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: open

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 13

Agitator: yes

Number of revolutions: 51

Power: 0,18

Internal diameter tank: 390 mm

Outer diameter tank: 600 mm

Cylinder height: 440 mm

Total height of tank: 2.030 mm

SKU: 484190



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control

Additional Information2: cabinet partially incomplete (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 60

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 440 mm

Internal diameter: 390 mm

Total Height: 2,030 mm

Outer diameter: 600 mm



Stirrer

Power (kW): 0,18

Speed (RPM): 51

Mer

Heat Exchanger: RVS 304

Isolated: Yes