6000 liter tank in Acid-proof 316

212 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Volumetric volume (L): 6.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 100 °C

Min. temperature (°C): -20 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Top type: conical
Shape of tank: cylindrical
Bottom type: conical

Total discharge: yes
Fixation points: 4 adjustable feet
Type of HE on the cylinder: dimple-jacket
Water pressure HE: 12 Bar
Hydraulic test pressure: 40 Bar

Working temperature HE cylinder: -20 °C
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 316
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 316 (V4A)

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top

Number of revolutions: 98
Power: 0,37

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Voltage: three-phase
Internal diameter tank: 1.800 mm
Outer diameter tank: 1.900 mm

Total height of tank: 5.400 mm
Empty weight tank: 1.200

SKU: 383567

Mer information

Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: isolert med varmeveksler
Max. Service Temperature: 100 °C
Min. Operating Temperature: -20 °C
Mobile Tank: No, it is not.
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Tank Shape: cylindrical
Complete Drainage: Yes
Bottom Type: conical
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 6000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304
Material vätskeberörd del på omrörare: SS AISI 316 (V4A)
Exterior cladding: RVS 304

Tank Dimensions

Internal diameter: 1.800 mm
Total Height: 5,400 mm
Outer diameter: 1.900 mm

Heat exchangers

Operating Temperature Heat Exchanger Cylinder: -20 °C
Bottom hydrostatic test pressure: 40 bars
Hydrostatic test pressure: 40 bars
Type of Heat Exchanger on Cylinder: dimple jacket
Water Pressure Heat Exchanger: 12 bars

Stirrer

Power (kW): 0,37
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 98
Voltage: three-phase

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer
Isolated: Yes
Weight: 1.200

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor