

6000 liters tank in Stainless 304



97 000 SEK /st exkl moms

Additional information: Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos); Functionality of the double jacket not checked

Volumetric volume (L): 6.000 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Agitator: yes

Power: 1,50

Internal diameter tank: 2.120 mm

Outer diameter tank: 2.270 mm

Cylinder height: 1.550 mm

Total height of tank: 3.450 mm

SKU: 419069

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos) ; Functionality

Additional Information2: of the double jacket not checked; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 6000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.550 mm

Internal diameter: 2.120 mm

Total Height: 3.450 mm

Outer diameter: 2,270 mm



Stirrer

Power (kW): 1,50

Mer

Isolated: Yes
